

SAPPHIRE SBS TORCH ON MEMBRANE

Flexible Waterproofing Membrane

SAPPHIRE SBS HAS BEEN DESIGNED TO MEET ALL CLIMATIC DEMANDS AND IS SOLD AS A SYSTEM IN EUROPE, THE MIDDLE AND FAR EAST.

With long-lasting and durable qualities unrivalled in its class, Sapphire SBS offers the building owner and contractor security and is supported by a range of Guarantees and Warranties - 12 year.

1. APPLICATIONS

- Asphalt Overlay's
 - Partial Bonded System
 - Mechanically Fixed System
 - Timber Deck Direct Application**
 - Inverted Roofing
 - Fully Bonded Insulated System
 - Mineral Overlay
- ** when applied to T.D Underlay

2. TYPICAL PERFORMANCE DATA

Tensile strength	670 N/5cm
Elongation at breaking point of	45%
Low Temperature Flexibility (Composite)	-15°C.
Thermal Stability	+100°C

3. GUARANTEED DURABILITY

Fire Safety

When incorporated in a Euro Polymers Specification, and as described in Table A5 of part B of the fire safety in buildings regulations 1991, Sapphire SBS Membranes are un-restricted in their use in relation to fire.

Production

The processes used in the production of Sapphire SBS are in accordance with M. O. A. T No 31 1984. The whole production process has been independently assessed to meet ISO9001.

Compatibility

Sapphire SBS is compatible with all products that are normally found on a roofing site. The products that should not be brought into contact with any bitumen based products are hydro-carbon solvents such as creosote and paraffin.



Auditing Workmanship & Materials



EUROTORCH

europOLYMERSGB Wychwood House, 34 Low Hall Road, Horsforth, Leeds LS18 4EF

Tel: 0113 259 0777 • Fax: 0113 259 1010 • info@europolymers-gb.com • www.europolymers-gb.com

SAPPHIRE SBS TORCH ON MEMBRANE

Flexible Waterproofing Membrane

Data Sheet
No.403

Issue Date:
January 2010

4. PRODUCT SELECTOR

Product	Code	Application	Finish	Roll Size	Nominal Weight
SBS U/Lay	EP210	Underlay	Sand	10x1M	2.5kg
SBS Sanded	EP211	Capping or U/lay	Sand	8x1M	4.5kg
SBS Nat/Slate	EP212	Capping sheet	Mineral	8x1M	4.5kg
SBS Charcoal	EP213	Capping sheet	Mineral	8x1M	4.5kg
SBS Cork	EP214	Capping sheet	Mineral	8x1M	4.5kg
SBS Blue/ Grey	EP215	Capping sheet	Mineral	8x1M	4.5kg

Complementary Products

- Universal Venting Layer
- Uni-Vap Vapour Control Layer
- T. D Underlay (Timber Deck)
- Asphalt Levelling Compound
- E. P. Primer
- E. P. Coolface Insulation Products

Coloured membranes are produced to order and are subject to an extended delivery time.

5. GUARANTEES AND WARRANTIES

12 Year Guarantees and Warranties

Euro Polymers offers a range of Guarantees and Warranties to suit the clients requirements.

AWM Protector, Pathfinder and Pioneer Warranties offer varying levels of term and cover.

Contact Euro Polymers for details.

europolymerSGB Wychwood House, 34 Low Hall Road, Horsforth, Leeds LS18 4EF

Tel: 0113 259 0777 • Fax: 0113 259 1010 • info@europolymerS-gb.com • www.europolymerS-gb.com

All products should be sold in accordance with the manufacturer's instructions. No responsibility can be taken by the manufacturers where conditions of use are beyond our control. Euro Polymers products are available for sale in accordance with Euro Polymers standard conditions of sale which are available on request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us or our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of the supplied product